


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 650/60 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D

## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	660	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1845	<b>RIM ALT</b>	DW21B
<b>SLR (MM)</b>	834	<b>ECE</b>	E11-106R-008774
<b>RC (MM)</b>	5564	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2800	3230	3715	4140	4630	5055	5665	6095
<b>FROM 65 TO 40</b>	3080	3550	4085	4555	5090	5560	6230	6700
30	3140	3615	4165	4640	5190	5665	6350	6830
20	3200	3690	4245	4735	5290	5780	6475	6965
10	3390	3905	4495	5010	5600	6115	6850	7370
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	4310	4970	5720	6375	7125	7785	8720	9380
10 HT	3140	3615	4165	4640	5190	5665	6350	6830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.