


# AS 504

<b>TIRE SIZE</b>	<b>10.0/80 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	109 A8
<b>LI/SS FREE ROLLING</b>	121 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94063963	<b>RC (IN)</b>	87.9
<b>SW (IN)</b>	10.6	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	28.7	<b>RIM ALT</b>	7.0
<b>SLR (IN)</b>	13.2	<b>ECE</b>	E11-106R-006010

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	57
5 FR	4480
15 FR	3800
20 FR	3580
25 FR	3200
5 DW	3180
15 DW	2700
20 DW	2545
25 DW	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.