

# COLT

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 7.50 - 15   |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | LEICHT-LKW / ANHÄNGER /<br>LANDWIRTSCHAFTLICHE GERÄTE /<br>ANHÄNGER |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## ABMESSUNGEN IS STANDARD

|                 |     |                |      |
|-----------------|-----|----------------|------|
| <b>SW (MM)</b>  | 217 | <b>RIM REC</b> | 6.00 |
| <b>OD (MM)</b>  | 790 | <b>PR</b>      | 16   |
| <b>SLR (MM)</b> | 0   |                |      |
| <b>RC (MM)</b>  | 0   |                |      |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>7.50</b> |
|-------------------|-------------|
| <b>100 LS</b>     | 1500        |
| <b>100 LD</b>     | 1440        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.