


MULTIMAX MP 529

TIRE SIZE	400/70 R 20 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TELESKOPLADER
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	149 A8/B



ABMESSUNGEN IS STANDARD

SW (MM)	415	RIM REC	13
OD (MM)	1090	RIM ALT	12 SDC;13SDC;14
SLR (MM)	500	ECE	E11-106R-0010769
RC (MM)	3314	SRI	525

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.2	4.4
50	1550	1825	2100	2375	2650	2950	3250	-	-
40	1550	1825	2100	2375	2650	2950	3250	-	-
30	1660	1960	2265	2570	2870	3175	3480	-	-
25	1730	2040	2355	2670	2980	3295	3610	-	-
10 CYC.	1910	2335	2760	3180	3605	4030	4455	4670	4880
STATIC	2930	3580	4230	4880	5530	6180	6830	7155	7480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.