DATA SHEET

PRINTED ON
21-04-2026

EARTHMAX SR 30

TIRE SIZE	**15.5 R 25**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	KNICKGELENKTER MULDENKIPPER / PLANIERER / RADLADER
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	160 B ; 169 A2

ABMESSUNGEN IS STANDARD

OD (MM)	1276	**TRA CODE**	E3/L3
SLR (MM)	574	**STAR RATING**	★★/★
RC (MM)	3809		
RIM REC	12.00/1.3		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25
50	3650	3875	4000	4250	4375	4500
10	5000	5150	5450	5600	5800	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..