


AW 711

TIRE SIZE	440/55 R 18
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COSECHADORA / MAQUINARIA AGRÍCOLA / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STUBBLE RESISTANT
TIRE TYPE	TL
LI/SS	159 A8/B



DIMENSIONES IS STANDARD

SW (MM)	410	RIM REC	14
OD (MM)	945	RIM ALT	13
SLR (MM)	432	ECE	E4-106R-001398
RC (MM)	2893	SRI	450

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	1315	1710	2100	2410	2800	3195	3415	3765	4115	4375
40	1315	1710	2100	2410	2800	3195	3415	3765	4115	4375
30	1470	1915	2355	2695	3140	3580	3825	4215	4610	4900
25	1565	2035	2505	2870	3335	3805	4065	4485	4900	5210
20	1655	2155	2650	3035	3530	4030	4305	4745	5185	5515
10	1840	2390	2940	3370	3920	4475	4780	5270	5760	6125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.