

EARTHMAX SR 49



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 49



EARTHMAX SR 49 is an All Steel radial tire that has been engineered for loaders and dozers, low profile dump trucks (LPDT) and load haul dumps (LHD). EARTHMAX SR 49 provides optimum performance in severe mining operations requiring exceptional traction and stability. The tire has a directional pattern and is made of a special cut-resistant compound providing excellent durability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø33"	35/65 R 33	TL	L4	**	224 A2	28.00/3.5	--	0	35.4	81.1	35.0	241.1	74.34	CR
	35/65 R33	TL	L4	***	229 A2	28.00/3.5	--	0	35.4	81.1	35.0	241.1	74.34	CR
	35/65 R 33	TL	SH4	****	-	28.00/3.5	--	0	35.4	81.1	35.0	241.1	74.34	CR
	35/65 R33	TL	E4/L4	****/**	-	28.00/3.5	--	0	35.4	81.1	35.0	241.1	74.34	CR
Ø45"	45/65 R 45	TL	L4	**	245 A2	36.00/4.5	-	0	44.5	107.5	46.9	319.4	90.72	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
E4/L4/SH4		A2	
245 lbs		A2	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width O.O. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index