

EARTHMAX SR 32



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 32

EARTHMAX SR 32 is a non-directional wide-base radial tyre particularly suitable for scrapers. The tyre features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø29"	29.5 R 29	TL	E3	**	202 B	25.00/3.5	24.00/3.5	288	765	1980	883	6009	48	CR
	33.25 R 29	TL	E3	**	209 B	27.00/3.5	26.00/3.5	346	845	2080	915	6250	54	CR
Ø35"	37.25 R 35	TL	E3	**	218 B	31.00/4.0	-	453	963	2381	1062	7229	59	CR
Ø39"	40.5/75 R39	TL	E3	**	225 B	32.00/4.5	-	689	985	2610	1164	7924	59	STD

STD: STANDARD, CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.D. 2%–5.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
40.5/75 R39	TL	E3	**	225 B	32.00/4.5	-	505	985	2610	1164	7924	59	CR

STD: STANDARD, CR: CUT RESISTANT COMPOUND



TECHNOLOGIES				PERFORMANCES		
						
						
B	225 kg					

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026