

# AT 603

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ARBETSFORDON / GRÄVLASTARE / ARBETSFORDON / GRÄVLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8
<b>LI/SS FREE ROLLING</b>	150 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94031269	<b>RC (IN)</b>	119.2
<b>SW (IN)</b>	12.1	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	39.4	<b>RIM ALT</b>	11
<b>SLR (IN)</b>	17.6	<b>ECE</b>	E11-106R-004352

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	80
5 FR	10340
15 FR	8780
20 FR	8270
25 FR	7390
5 DW	7290
15 DW	6190
20 DW	5830
25 DW	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.