

# FLOTATION 648

<b>TIRE SIZE</b>	<b>800/45 - 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	170 A8/167 B
<b>LI/SS FREE ROLLING</b>	183 A8/180 B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	800	<b>RIM REC</b>	AG 28.00
<b>OD (MM)</b>	1393	<b>ECE</b>	E11-106R-004618
<b>SLR (MM)</b>	631	<b>PR</b>	20
<b>RC (MM)</b>	4185		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60	2.70	2.80
10 FR	11730	11990	12250
20 FR	10560	10790	11025
30 FR	9385	9595	9800
40 FR	8380	8565	8750
50 FR	7540	7710	8000
10 DW	8045	8225	8400
20 DW	7240	7405	7560
30 DW	6435	6580	6720
40 DW	5745	5875	6000
50 DW	5170	5290	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.