


# AGRIMAX RT 955

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>300/95 R 46</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 148 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                             |
|-----------------|----------|----------------|-----------------------------|
| <b>USA CODE</b> | 94021871 | <b>RC (IN)</b> | 209.4                       |
| <b>SW (IN)</b>  | 11.6     | <b>RIM REC</b> | W 9                         |
| <b>OD (IN)</b>  | 68.4     | <b>RIM ALT</b> | W 10 ; W 11 ; DW 10 ; DW 11 |
| <b>SLR (IN)</b> | 32.0     | <b>ECE</b>     | E4-106R-000790              |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 64    |
|-----------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| 30        | 2440 | 2850 | 3270 | 3680 | 4100 | 4450 | 4860 | 5210 | 5700 | 6180 | 6600 | 6950 | -     |
| 25        | 2440 | 2850 | 3270 | 3680 | 4100 | 4450 | 4860 | 5210 | 5700 | 6180 | 6600 | 6950 | -     |
| 20        | 2610 | 3050 | 3510 | 3950 | 4400 | 4760 | 5210 | 5590 | 6110 | 6620 | 7080 | 7440 | -     |
| 10        | 3000 | 3510 | 4020 | 4530 | 5050 | 5470 | 5990 | 6420 | 7010 | 7610 | 8120 | 8540 | -     |
| 5         | 3360 | 3940 | 4510 | 5090 | 5670 | 6140 | 6710 | 7200 | 7870 | 8540 | 9120 | 9590 | 10420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.