


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 420/80 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 159 D ; 170 A2 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 418 | RIM REC | W 13 |
| OD (MM) | 1840 | RIM ALT | W 12 |
| SLR (MM) | 863 | ECE | E4-106R-001489 |
| RC (MM) | 5641 | SRI | 900 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65 | 1625 | 1865 | 2140 | 2415 | 2695 | 2970 | 3210 | 3450 | 4070 | 4375 |
| 50 | 1705 | 1960 | 2250 | 2540 | 2830 | 3120 | 3375 | 3625 | 4275 | 4595 |
| 40 | 1780 | 2045 | 2345 | 2650 | 2950 | 3255 | 3520 | 3780 | 4460 | 4795 |
| 30 | 1870 | 2145 | 2465 | 2780 | 3100 | 3415 | 3695 | 3970 | 4685 | 5035 |
| 10 | 2235 | 2565 | 2945 | 3325 | 3705 | 4085 | 4420 | 4750 | 5580 | 6000 |
| 10 LT | 2175 | 2500 | 2870 | 3240 | 3610 | 3980 | 4305 | 4625 | 5455 | 5865 |
| 10 HT | 1870 | 2145 | 2465 | 2780 | 3100 | 3415 | 3695 | 3970 | 4685 | 5035 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.