

EARTHMAX SR 42



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 42



EARTHMAX SR 42 is a radial OTR tire specially engineered for haul trains in mining and logging applications. The distinctive tread design provides outstanding traction and lateral stability as well as good braking and cornering performance on rough and gravel terrains even on ice and snow. Indeed, the special cut-and-wear-resistant tread compound is particularly suitable in extreme cold climate. EARTHMAX SR 42 features an All Steel casing for excellent durability and a long service life.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø24"	14.00 R 24	TL	E4	***	171 B	10.00W	--	105	380	1412	652	4231	38	CR
Ø25"	14.00 R 25	TL	E4	***	171 B	10.00/2.0	--	105	380	1412	652	4231	38	CR
	14.00 R 25	TL	E4	***	171 B	10.00/1.5	--	105	380	1412	652	4231	38	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
		Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	