


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	141 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	329	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1408	<b>RIM ALT</b>	W 9; W 10
<b>SLR (MM)</b>	645	<b>ECE</b>	E4-106R-000758
<b>RC (MM)</b>	4280	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
<b>50</b>	930	1085	1420	1730	1880	2010	2190	2370	2575
<b>40</b>	930	1085	1420	1730	1880	2010	2190	2370	2575
<b>30</b>	995	1160	1520	1850	2015	2155	2350	2540	2760
<b>10 LT</b>	1245	1455	1905	2315	2525	2695	2940	3180	3455
<b>10 HT</b>	995	1160	1520	1850	2015	2155	2350	2540	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.