

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>460/85 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	145 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94021765	<b>RC (IN)</b>	179.6
<b>SW (IN)</b>	18.7	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	60.8	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (IN)</b>	26.8	<b>ECE</b>	E4-106R-000774

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	3520	4100	4670	5250	5820	6390
<b>25</b>	3520	4100	4670	5250	5820	6390
<b>20</b>	3770	4390	5000	5620	6240	6840
<b>5 LT</b>	4720	5490	6260	7030	7800	8580
<b>5 HT</b>	3770	4290	5000	5620	6240	6840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.