


AGRIMAX V-FLECTO



TIRE SIZE	VF 650/60 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	174 D

DIMENSIONER IS STANDARD

SW (MM)	660	RIM REC	DW 23 B
OD (MM)	1845	RIM ALT	DW21B
SLR (MM)	834	ECE	E11-106R-008774
RC (MM)	5564	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2800	3230	3715	4140	4630	5055	5665	6095
FROM 65 TO 40	3080	3550	4085	4555	5090	5560	6230	6700
30	3140	3615	4165	4640	5190	5665	6350	6830
20	3200	3690	4245	4735	5290	5780	6475	6965
10	3390	3905	4495	5010	5600	6115	6850	7370
*UPTO 10 CYC WITH FRONT LOADER	4310	4970	5720	6375	7125	7785	8720	9380
10 HT	3140	3615	4165	4640	5190	5665	6350	6830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.