

# EARTHMAX SR 46

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 27.00 R 49                                                                               |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ                                                                 |
| VERSION      | HEAT RESISTANT COMPOUND                                                                  |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 223 B                                                                                    |



## РАЗМЕРЫ US STANDARD

|          |          |             |           |
|----------|----------|-------------|-----------|
| USA CODE | 94055159 | RIM REC     | 19.50/4.0 |
| OD (IN)  | 105.8    | RIM ALT     | -         |
| SLR (IN) | 48.2     | TRA CODE    | E4        |
| RC (IN)  | 321.5    | STAR RATING | ★★        |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 45400 | 48100 | 49400 | 50700 | 52000 | 55100 | 56800 | 58400 | 60000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.