

# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 600/600 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 D

## DIMENSIONS US STANDARD

<b>CODE USA</b>	94074495	<b>RC (IN)</b>	185.4
<b>SW (IN)</b>	23.4	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	62.4	<b>RIM ALT</b>	DW 18 L; DW 21 B
<b>SLR (IN)</b>	27.2	<b>ECE</b>	E11-106R-008773

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4960	5780	6580	7400	8210	9030
<b>FROM 40 TO 25</b>	5460	6350	7240	8130	9030	9920
20	5560	6470	7390	8290	9200	10120
12	5670	6600	7530	8450	9380	10320
5	6000	6980	7960	8940	9920	10910
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7640	8880	10130	11390	12630	13890
5 HT	5560	6470	7390	8290	9200	10120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.