


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>600/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 D ; 162 A8



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1745	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	790	<b>ECE</b>	E4-106R-000623
<b>RC (MM)</b>	5247	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	2100	2450	2760	3065	3370	3635	4025	4375
<b>50</b>	2210	2575	2895	3220	3540	3815	4230	4595
<b>40</b>	2280	2660	2995	3325	3660	3945	4370	4750
<b>30</b>	2420	2820	3175	3525	3880	4180	4635	5035
<b>10 LT</b>	2820	3285	3695	4110	4520	4870	5400	5865
<b>10 HT</b>	2420	2820	3175	3525	3880	4180	4635	5035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.