

AGRIMAX RT 855

TIRE SIZE	420/80 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	165 A8/B



DIMENSIONS US STANDARD

USA CODE	94075508	RC (IN)	234.4
SW (IN)	16.5	RIM REC	W 13
OD (IN)	76.8	RIM ALT	W 12
SLR (IN)	36.0	ECE	E11-106R-0010078

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	20	23	29	35	41	46	52	58	64
30	4880	5460	6140	6700	7390	8740	8630	9310	9890	10450	11350
25	4880	5460	6140	6700	7390	7840	8630	9310	9890	10450	11350
20	5240	5840	6570	7180	7900	8400	9250	9980	10580	11190	12160
5 LT	6550	7310	8220	8980	9900	10500	11570	12490	13250	14010	15220
5 HT	5240	5840	6570	7180	7900	8400	9250	9980	10580	11190	12160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.