

MULTIMAX MP 515

405/70 R 20 MPT

| | |
|---------------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | GENEL KULLANIM ARACI / GÜBRE KAMYONU |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 136 G |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|----------------------------|
| SW (MM) | 407 | RIM REC | 13 |
| OD (MM) | 1076 | RIM ALT | 13 SDC; 12 SDC; 11 SDC; 11 |
| SLR (MM) | 493 | ECE | E4-54R-0016565 |
| RC (MM) | 3286 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.5 | 3.0 | 3.5 |
|------------|------|------|------|------|------|
| 90 | 1340 | 1580 | 1820 | 2040 | 2240 |
| 65 | 1455 | 1715 | 1975 | 2215 | 2435 |
| 40 | 1545 | 1820 | 2095 | 2350 | 2580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.