


FL 635

TIRE SIZE	750/45 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	168 D



DIMENSIONI IS STANDARD

SW (MM)	754	RIM REC	AG 24.00
OD (MM)	1247	ECE	E4-106R-002653
SLR (MM)	555	SRI	600
RC (MM)	3810		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1635	1865	2095	2605	2960	3420	3880	4235	4645	5100
65	1795	2050	2300	2860	3250	3755	4260	4650	5100	5600
50	2170	2475	2780	3460	3935	4545	5155	5630	6170	6780
40	2440	2785	3125	3890	4420	5110	5795	6325	6935	7620
30	2710	3090	3470	4315	4910	5670	6430	7025	7700	8460
25	2835	3235	3630	4515	5135	5930	6730	7350	8055	8850
10	3230	3685	4135	5145	5850	6755	7665	8370	9175	10080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.