


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 11.0/65 - 12 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 101 A8 |
| LI/SS FREE ROLLING | 114 A8 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 273 | RIM REC | 9.00 |
| OD (MM) | 700 | ECE | E4-106R-002834 |
| SLR (MM) | 321 | PR | 8 |
| RC (MM) | 2072 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.90 |
|------------|------|
| 10 FR | 1650 |
| 25 FR | 1405 |
| 30 FR | 1320 |
| 40 FR | 1180 |
| 10 DW | 1155 |
| 25 DW | 980 |
| 30 DW | 925 |
| 40 DW | 825 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.