

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>340/85 R 28</b> |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 127 A8/B           |

### DIMENSIUNI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 353  | <b>RIM REC</b> | W 12           |
| <b>OD (MM)</b>  | 1289 | <b>RIM ALT</b> | W 11           |
| <b>SLR (MM)</b> | 599  | <b>ECE</b>     | E4-106R-000759 |
| <b>RC (MM)</b>  | 3908 | <b>SRI</b>     | 625            |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 965  | 1120 | 1280 | 1435 | 1595 | 1750 |
| <b>40</b>    | 965  | 1120 | 1280 | 1435 | 1595 | 1750 |
| <b>30</b>    | 1035 | 1200 | 1370 | 1540 | 1710 | 1875 |
| <b>10 LT</b> | 1290 | 1505 | 1715 | 1925 | 2135 | 2345 |
| <b>10 HT</b> | 1035 | 1200 | 1370 | 1540 | 1710 | 1875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

