

# AGRIMAX RT 955

|                  |                                                          |
|------------------|----------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>300/95 R 52</b>                                       |
| <b>UM</b>        | US STANDARD                                              |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>HARVESTER / IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                 |
| <b>TL/TT</b>     | TL                                                       |
| <b>LI/SS</b>     | 151 A8/B                                                 |



## DIMENSIONS US STANDARD

|                 |          |                |                             |
|-----------------|----------|----------------|-----------------------------|
| <b>USA CODE</b> | 94029747 | <b>RC (IN)</b> | 227.3                       |
| <b>SW (IN)</b>  | 11.6     | <b>RIM REC</b> | W 9                         |
| <b>OD (IN)</b>  | 74.4     | <b>RIM ALT</b> | W 10 ; W 11 ; DW 10 ; DW 11 |
| <b>SLR (IN)</b> | 35.0     | <b>ECE</b>     | E4-106R-001484              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58    | 64    |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 30        | 2980 | 3880 | 4720 | 5180 | 5480 | 6020 | 6550 | 7080 | 7600  | -     |
| 25        | 2980 | 3880 | 4720 | 5180 | 5480 | 6020 | 6550 | 7080 | 7600  | -     |
| 20        | 3190 | 4160 | 5060 | 5540 | 5870 | 6440 | 7010 | 7580 | 8150  | -     |
| 5         | 3540 | 4450 | 5480 | 6500 | 7540 | 7760 | 8670 | 9590 | 10500 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.