

# LG 306

|                     |                                  |
|---------------------|----------------------------------|
| <b>TIRE SIZE</b>    | <b>16X6.50 - 8</b>               |
| <b>UM</b>           | US STANDARD                      |
| <b>CONSTRUCTION</b> | BIAS                             |
| <b>MACHINERY</b>    | TOSAERBA / TRATTORINO / TRATTORE |
| <b>VERSIONE</b>     | ARAMID BELTED                    |
| <b>TIRE TYPE</b>    | TL                               |



## DIMENSIONI US STANDARD

|                   |          |                |                              |
|-------------------|----------|----------------|------------------------------|
| <b>CODICE USA</b> | 94012756 | <b>RC (IN)</b> | 46.6                         |
| <b>SW (IN)</b>    | 6.7      | <b>RIM REC</b> | 5.375 I - 55; I - 70; I - 90 |
| <b>OD (IN)</b>    | 16.1     | <b>ECE</b>     | E11-106R-003499              |
| <b>SLR (IN)</b>   | 7.2      | <b>PR</b>      | 6                            |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>42</b> |
| 10               | 785       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.