


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>440/65 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	138 D ; 141 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	441	<b>RIM REC</b>	W 14 L
<b>OD (MM)</b>	1080	<b>RIM ALT</b>	W 13 ; W 15 L
<b>SLR (MM)</b>	479	<b>ECE</b>	E4-106R-000760
<b>RC (MM)</b>	3240	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1110	1300	1490	1655	1820	1960	2175	2360
<b>50</b>	1170	1365	1565	1740	1910	2060	2285	2480
<b>40</b>	1215	1420	1625	1805	1985	2140	2370	2575
<b>30</b>	1280	1495	1715	1905	2095	2255	2500	2715
<b>10 LT</b>	1490	1745	1995	2220	2440	2630	2915	3165
<b>10 HT</b>	1280	1495	1715	1905	2095	2255	2500	2715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.