

AGRIMAX RT 657

TIRE SIZE	420/65 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	136 D ; 139 A8



DIMENSIONER IS STANDARD

SW (MM)	418	RIM REC	W 13
OD (MM)	1308	RIM ALT	W 12; W 11
SLR (MM)	606	ECE	E11-106R-002975
RC (MM)	3952	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1055	1210	1390	1570	1750	1930	2085	2240
50	1110	1275	1465	1650	1840	2030	2195	2355
40	1145	1315	1510	1705	1900	2090	2260	2430
30	1215	1395	1600	1810	2015	2220	2400	2580
10 LT	1415	1625	1865	2105	2345	2585	2795	3005
10 HT	1215	1395	1600	1810	2015	2220	2400	2580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.