


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>340/80 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	140 A8 ; 135 D



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94033843	<b>RC (IN)</b>	135.6
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	DW 11
<b>OD (IN)</b>	45.4	<b>RIM ALT</b>	W 10 ; W 12 ; DW 10
<b>SLR (IN)</b>	20.5	<b>ECE</b>	E4-106R-002293

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	2260	2790	3260	3790	4280	4810
30	2440	3010	3530	4090	4610	5180
25	2590	3200	3750	4350	4910	5510
20	2690	3330	3900	4530	5100	5730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.