


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	181 D



DIMENSIONES IS STANDARD

SW (MM)	715	RIM REC	DW 24 B
OD (MM)	1961	RIM ALT	DW 23 B; DW 25 B
SLR (MM)	843	ECE	E11-106R-006163
RC (MM)	5773	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3750	4350	4950	5625	6225	6825	7505
FROM 65 TO 40	4125	4785	5445	6185	6845	7505	8250
30	4205	4880	5550	6305	6980	7655	8415
20	4290	4975	5660	6430	7115	7805	8580
10	4535	5260	5985	6800	7525	8255	9075
*UPTO 10 CYC WITH FRONT LOADER	5775	6695	7620	8655	9580	10505	11550
10 HT	4205	4880	5550	6305	6980	7655	8415

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.