

# AGRIMAX RT 955

|                  |                                                          |
|------------------|----------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>230/95 R 44</b>                                       |
| <b>UM</b>        | IS STANDARD                                              |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>HARVESTER / IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                 |
| <b>TL/TT</b>     | TL                                                       |
| <b>LI/SS</b>     | 134 A8/B                                                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 228  | <b>RIM REC</b> | W 7            |
| <b>OD (MM)</b>  | 1556 | <b>RIM ALT</b> | W 8            |
| <b>SLR (MM)</b> | 739  | <b>ECE</b>     | E4-106R-000777 |
| <b>RC (MM)</b>  | 4788 | <b>SRI</b>     | 750            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|-----|------|------|------|------|------|------|------|------|------|
| <b>50</b>  | 830 | 1085 | 1315 | 1445 | 1530 | 1675 | 1825 | 1975 | 2120 | -    |
| <b>40</b>  | 830 | 1085 | 1315 | 1445 | 1530 | 1675 | 1825 | 1975 | 2120 | -    |
| <b>30</b>  | 890 | 1160 | 1410 | 1545 | 1635 | 1795 | 1955 | 2115 | 2270 | -    |
| <b>10</b>  | 990 | 1245 | 1530 | 1815 | 2100 | 2165 | 2420 | 2675 | 2930 | 3180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.