


AGRIMAX PROHARVEST

| | |
|--------------|--|
| TIRE SIZE | VF 1020/55 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COSECHADORA |
| VERSIÓN | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 200 D |



DIMENSIONES US STANDARD

| | | | |
|------------|----------|---------|------------------------|
| CÓDIGO USA | 94515097 | RIM REC | 36.00 VA (multi-piece) |
| SW (IN) | 39.8 | ECE | E11-106R-0011309 |
| OD (IN) | 81.1 | | |
| RC (IN) | 2.2 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 10960 | 12640 | 14330 | 16290 | 17980 | 19950 | 22190 | 22470 | 26120 | 28090 |
| FROM 40 TO 25 | 12040 | 13890 | 15740 | 17900 | 19750 | 21910 | 24380 | 24690 | 28700 | 30860 |
| 20 | 12280 | 14170 | 16060 | 18260 | 20150 | 22350 | 24880 | 25190 | 29290 | 31480 |
| 12 | 12520 | 14450 | 16380 | 18620 | 20550 | 22790 | 25360 | 25680 | 29860 | 32100 |
| 5 | 13250 | 15280 | 17320 | 19700 | 21740 | 24110 | 26830 | 27160 | 31580 | 33950 |
| *UPTO 20 CYC | 13670 | 15770 | 17870 | 20330 | 22420 | 24880 | 27680 | 28030 | 32580 | 35030 |
| *UPTO 10 CYC | 16310 | 18830 | 21330 | 24260 | 26770 | 29690 | 33050 | 33460 | 38900 | 41820 |
| *UPTO 5 CYC | 17880 | 20630 | 23380 | 26590 | 29340 | 32550 | 36210 | 36670 | 42620 | 45830 |
| 10HT | 12280 | 14170 | 16060 | 18260 | 20150 | 22350 | 24880 | 25190 | 29290 | 31480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.