

# TR 128

5 - 12

|                     |  |
|---------------------|--|
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | BIAS   |
| <b>MACHINERY</b>    | ROTOTILLER / GENEL KULLANIM ARACI<br>/ UYGULAMALI MAKINE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
|                     | 60 A8  |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94055883 | <b>RC (IN)</b> | 66.9            |
| <b>SW (IN)</b>  | 5.0      | <b>RIM REC</b> | 4 JA            |
| <b>OD (IN)</b>  | 21.8     | <b>ECE</b>     | E11-106R-005189 |
| <b>SLR (IN)</b> | 10.3     | <b>PR</b>      | 6               |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>52</b> |
| 25               | 550       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.