

AGRIMAX V-FLECTO

TYRE SIZE	VF 710/75 R 38
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	183 D



DIMENSIONS IS STANDARD

SW (MM)	720	RIM REC	DW 24 B
OD (MM)	2060	RIM ALT	DW 23 B ; DW 25 B
SLR (MM)	905	ECE	E11-106R-006764
RC (MM)	6151	SRI	950

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3980	4615	5255	5965	6605	7240	7960
FROM 65 TO 40	4375	5075	5775	6560	7260	7960	8750
30	4460	5175	5890	6690	7405	8115	8925
20	4550	5275	6005	6820	7550	8275	9100
10	4810	5580	6350	7215	7985	8755	9625
*UPTO 10 CYC WITH FRONT LOADER	6125	7105	8085	9180	10160	11140	12250
10 HT	4460	5175	5890	6690	7405	8115	8925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.