

FLOTATION 648

TIRE SIZE	550/60 - 22.5
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	158 A8/154 B
LI/SS FREE ROLLING	171 A8/167 B



DIMENSÕES US STANDARD

CÓDIGO USA	94044474	RC (IN)	146.7
SW (IN)	21.7	RIM REC	AG 16.00
OD (IN)	48.8	ECE	E11-106R-004391
SLR (IN)	21.3	PR	20

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	48	49	51
5 FR	18330	18660	18980
10 FR	16500	16790	17080
20 FR	14670	14920	15190
25 FR	13090	13330	13560
30 FR	11780	11990	12010
5 DW	12660	12900	13120
10 DW	11400	11610	11810
20 DW	10140	10320	10490
25 DW	9050	9210	9370
30 DW	7990	8120	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.