

# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>320/85 R 32</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL                               |
| <b>MACHINERY</b>    | ОПРЫСКИВАТЕЛЬ / КОМБАЙН<br>ДЛЯ УБОРКИ ВИНОГРАДА /<br>ТРАКТОР-ТЯГАЧ / КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 126 A8/B   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94021598 | <b>RC (IN)</b> | 160.7          |
| <b>SW (IN)</b>  | 13.0     | <b>RIM REC</b> | W 11           |
| <b>OD (IN)</b>  | 53.4     | <b>RIM ALT</b> | W 9; W 10      |
| <b>SLR (IN)</b> | 24.4     | <b>ECE</b>     | E4-106R-000758 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 2060 | 2400 | 2740 | 3080 | 3420 | 3750 |
| <b>25</b>   | 2060 | 2400 | 2740 | 3080 | 3420 | 3750 |
| <b>20</b>   | 2220 | 2570 | 2930 | 3300 | 3660 | 4010 |
| <b>5 LT</b> | 2770 | 3220 | 3670 | 4120 | 4570 | 5030 |
| <b>5 HT</b> | 2220 | 2570 | 2930 | 3300 | 3660 | 4010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.