


RT 747 AGRO INDUSTRIAL

| | |
|---------------------|--|
| TIRE SIZE | 460/70 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 159 A8 ; 156 B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94059270 | RC (IN) | 151.2 |
| SW (IN) | 18.3 | RIM REC | DW 15 L |
| OD (IN) | 49.4 | RIM ALT | DW 14 L; DW 16 L |
| SLR (IN) | 21.9 | ECE | E11-106R-005105 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 51 | 58 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 3380 | 4170 | 4950 | 5640 | 6430 | 7200 | 7730 | 8820 |
| 25 | 3760 | 4630 | 5500 | 6270 | 7140 | 8000 | 8590 | 9640 |
| 20 | 3910 | 4820 | 5720 | 6530 | 7430 | 8320 | 8930 | 10030 |
| 15 | 3980 | 4910 | 5830 | 6650 | 7570 | 8490 | 9100 | 10230 |
| 5 CYC | 5640 | 6940 | 8260 | 9410 | 10710 | 12000 | 12890 | 14470 |
| STATIC | 8640 | 10650 | 12650 | 14430 | 16420 | 18410 | 19750 | 22190 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.