

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | IF 480/95 R 50                                                                           |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR                                              |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 170 D                                                                                    |



## DIMENSIONS IS STANDARD

|          |      |          |                 |
|----------|------|----------|-----------------|
| SW (MM)  | 479  | RIM REC  | DW 16 B         |
| OD (MM)  | 2170 | ECE      | E11-106R-004898 |
| SLR (MM) | 1002 | SRI      | 1025            |
| RC (MM)  | 6574 | TRA CODE | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------------------------|------|------|------|------|------|------|------|------|
| 70                             | 2565 | 2945 | 3385 | 3820 | 4255 | 4695 | 5130 | 5460 |
| FROM 65 TO 40                  | 2820 | 3240 | 3720 | 4200 | 4680 | 5160 | 5640 | 6000 |
| 30                             | 2930 | 3365 | 3865 | 4365 | 4865 | 5365 | 5865 | 6240 |
| 20                             | 3045 | 3495 | 4015 | 4535 | 5050 | 5570 | 6090 | 6480 |
| 10                             | 3580 | 4110 | 4720 | 5330 | 5940 | 6550 | 7160 | 7620 |
| *UPTO 10 CYC WITH FRONT LOADER | 3945 | 4535 | 5205 | 5880 | 6550 | 7220 | 7895 | 8400 |
| 10HT                           | 2930 | 3365 | 3865 | 4365 | 4865 | 5365 | 5865 | 6240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.