

# EM 936

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>16.0/70 -20</b>                      |
| <b>UM</b>           | IS STANDARD                             |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                  |
| <b>MACHINERY</b>    | ESCAVATORE / SOLLEVATORE<br>TELESCOPICO |
| <b>VERSIONE</b>     | SPECIAL                                 |
| <b>TIRE TYPE</b>    | TT                                      |
| <b>LI/SS</b>        | 149 B ; 166 A2                          |



## DIMENSIONI IS STANDARD

|                 |        |                 |    |
|-----------------|--------|-----------------|----|
| <b>OD (MM)</b>  | 1090   | <b>RIM ALT</b>  | 13 |
| <b>SLR (MM)</b> | 480    | <b>PR</b>       | 14 |
| <b>RC (MM)</b>  | 3295   | <b>TRA CODE</b> | E2 |
| <b>RIM REC</b>  | 13 SDC |                 |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.50 | 4.50 |
|------------|------|------|
| 50         | 3250 | -    |
| 10         | -    | 5300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.