


# AW 909

|                           |  |
|---------------------------|--|
| <b>TYRE SIZE</b>          | 10.0/75 - 15.3   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS   |
| <b>VERSION</b>            | STANDARD   |
| <b>TYRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 123 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94010394 | <b>RC (IN)</b> | 87.7           |
| <b>SW (IN)</b>  | 10.8     | <b>RIM REC</b> | 9.00           |
| <b>OD (IN)</b>  | 29.9     | <b>ECE</b>     | E4-106R-001540 |
| <b>SLR (IN)</b> | 13.5     | <b>PR</b>      | 10             |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 57   |
|-----------|------|
| 5 FR      | 4780 |
| 15 FR     | 4070 |
| 20 FR     | 3820 |
| 25 FR     | 3420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.