

# MP 585

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | 12.5 - 20                             |
| <b>UM</b>           | US STANDARD                           |
| <b>CONSTRUCTION</b> |                                       |
| <b>MACHINERY</b>    | UNIVERSAL VEHICLE / UNIVERSAL VEHICLE |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TL                                    |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94038404 | <b>RC (IN)</b> | 123.2          |
| <b>SW (IN)</b>  | 13.2     | <b>RIM REC</b> | 11             |
| <b>OD (IN)</b>  | 41.3     | <b>RIM ALT</b> | 12 SDC         |
| <b>SLR (IN)</b> | 18.9     | <b>ECE</b>     | E4-54R-0022635 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51   |
|-----------|------|
| 55        | 4410 |
| 30        | 4940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.