

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 140 D |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94062287 | RC (IN) | 164.8 |
| SW (IN) | 18.9 | RIM REC | W 15 L |
| OD (IN) | 55.9 | RIM ALT | W 14 L; W 16 L |
| SLR (IN) | 25.0 | ECE | E11-106R-005521 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 3030 | 3530 | 4020 | 4520 | 5020 | 5510 |
| 30 | 3190 | 3700 | 4230 | 4750 | 5270 | 5790 |
| 25 | 3330 | 3780 | 4420 | 4960 | 5500 | 6040 |
| 20 | 3490 | 4060 | 4630 | 5200 | 5780 | 6340 |
| 5 LT | 4070 | 4730 | 5400 | 6060 | 6720 | 7390 |
| 5 HT | 3490 | 4060 | 4630 | 5200 | 5780 | 6340 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.