

AGRIMAX RT 765

TIRE SIZE	710/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR / TRACTOR / VENDIMIADORA / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	173 D ; 176 A8



DIMENSIONES IS STANDARD

SW (MM)	716	RIM REC	DW 23 B
OD (MM)	2061	RIM ALT	DW 25 B
SLR (MM)	922	ECE	E4-106R-000807
RC (MM)	6174	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3120	3640	4095	4550	5005	5395	5980	6500
50	3280	3825	4300	4780	5260	5665	6280	6825
40	3410	3980	4475	4970	5470	5895	6535	7100
30	3590	4190	4710	5235	5760	6205	6880	7475
10 LT	4185	4880	5490	6100	6710	7230	8015	8710
10 HT	3590	4190	4710	5235	5760	6205	6880	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.