


AGRIMAX FORCE

| | |
|---------------------|--|
| TIRE SIZE | IF 710/60 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / HIGH-POWER TRACTOR / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|-----------------|----------------|
| SW (MM) | 708 | RIM REC | DW 25 B |
| OD (MM) | 1614 | ECE | E4-106R-001407 |
| SLR (MM) | 714 | SRI | 775 |
| RC (MM) | 4814 | TRA CODE | R1W |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|----------------------|------|------|------|------|------|------|------|------|
| 70 | 2340 | 2695 | 3105 | 3460 | 3870 | 4225 | 4735 | 5095 |
| FROM 65 TO 40 | 2575 | 2965 | 3415 | 3805 | 4255 | 4645 | 5205 | 5600 |
| 30 | 2675 | 3080 | 3550 | 3955 | 4425 | 4830 | 5410 | 5820 |
| 20 | 2780 | 3200 | 3685 | 4105 | 4595 | 5015 | 5620 | 6045 |
| 10 | 3270 | 3765 | 4335 | 4830 | 5400 | 5895 | 6610 | 7110 |
| UPTO 30 CYC | 3345 | 3850 | 4435 | 4945 | 5530 | 6035 | 6765 | 7280 |
| UPTO 15 CYC | 3990 | 4595 | 5290 | 5895 | 6595 | 7195 | 8065 | 8680 |
| UPTO 10 CYC | 4375 | 5040 | 5805 | 6465 | 7230 | 7895 | 8845 | 9520 |
| 10 HT | 2675 | 3080 | 3550 | 3955 | 4425 | 4830 | 5410 | 5820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.