


RIDEMAX FL 615

| | |
|---------------------|--|
| TIRE SIZE | VF 800/65 R 32 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | RIMORCHIO / AUTOBOTTE / SPARGITORE / ATTREZZI AGRICOLI |
| VERSIONE | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 190 D |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CODICE USA | 94513925 | RC (IN) | 220.9 |
| SW (IN) | 32.1 | RIM REC | DW 28 B |
| OD (IN) | 72.8 | RIM ALT | DW 27 B |
| SLR (IN) | 31.9 | ECE | E11-106R-0010408 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 |
|-----------|-------|-------|-------|-------|-------|-------|
| 40 | 11450 | 12850 | 15660 | 17770 | 20570 | 23370 |
| 30 | 13400 | 15050 | 18330 | 20790 | 24070 | 27350 |
| 25 | 14780 | 16590 | 20200 | 22920 | 26530 | 30150 |
| 20 | 16160 | 18130 | 22090 | 25050 | 29010 | 32960 |
| 15 | 16730 | 18770 | 22870 | 25940 | 30040 | 34130 |
| 10 | 17420 | 19540 | 23810 | 27010 | 31270 | 35530 |
| 5 | 18780 | 21090 | 25680 | 29130 | 33730 | 38330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.