

# MULTI RIB

|                     |                                                                      |
|---------------------|----------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | 11.00 - 16                                                           |
| <b>UM</b>           | IS STANDARD                                                          |
| <b>CONSTRUCTION</b> | ✠ BIAS                                                               |
| <b>MACHINERY</b>    | TVÅHJULSDRIVEN TRAKTOR /<br>ARBETSFORDON / TRAKTOR /<br>ARBETSFORDON |
| <b>VERSION</b>      | HD                                                                   |
| <b>TIRE TYPE</b>    | TL                                                                   |



## DIMENSIONER IS STANDARD

|                |            |           |    |
|----------------|------------|-----------|----|
| <b>SW (MM)</b> | 315        | <b>PR</b> | 12 |
| <b>OD (MM)</b> | 930        |           |    |
| <b>RIM REC</b> | W10 L      |           |    |
| <b>RIM ALT</b> | W 8; W 8 L |           |    |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.10</b> |
| 40                | 1550        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.