

# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>540/65 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 D ; 152 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1413	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	643	<b>ECE</b>	E4-106R-000650
<b>RC (MM)</b>	4253	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1560	1820	2050	2275	2505	2700	2990	3250
<b>50</b>	1640	1915	2155	2395	2630	2835	3145	3415
<b>40</b>	1705	1990	2240	2485	2735	2950	3270	3550
<b>30</b>	1800	2095	2360	2620	2880	3105	3445	3740
<b>10 LT</b>	2095	2440	2745	3050	3355	3615	4010	4355
<b>10 HT</b>	1800	2095	2360	2620	2880	3105	3445	3740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.