


FL 639

| | |
|---------------------|--|
| TIRE SIZE | 800/40 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRIDARE / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D ; 178 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 828 | RIM REC | AG 28.00 |
| OD (MM) | 1212 | ECE | E11-106R-0010830 |
| SLR (MM) | 538 | SRI | 575 |
| RC (MM) | 3642 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|-------|
| 70 | 1635 | 2095 | 2605 | 2960 | 3420 | 3880 | 4235 | 4645 | 5100 |
| 65 | 1795 | 2300 | 2860 | 3250 | 3755 | 4260 | 4650 | 5100 | 5600 |
| 50 | 2170 | 2780 | 3460 | 3935 | 4545 | 5155 | 5630 | 6170 | 6780 |
| 40 | 2400 | 3075 | 3825 | 4350 | 5025 | 5700 | 6225 | 6825 | 7500 |
| 30 | 2710 | 3470 | 4315 | 4910 | 5670 | 6430 | 7025 | 7700 | 8460 |
| 25 | 2835 | 3630 | 4515 | 5135 | 5930 | 6730 | 7350 | 8055 | 8850 |
| 10 | 3230 | 4135 | 5145 | 5850 | 6755 | 7665 | 8370 | 9175 | 10080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.