


MULTIMAX MP 522

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 28 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 156 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|---------------------------|
| CODE USA | 94052240 | RC (IN) | 168.4 |
| SW (IN) | 17.4 | RIM REC | DW 14 L |
| OD (IN) | 55.7 | RIM ALT | DW 13 ; DW 13 L ; DW 15 L |
| SLR (IN) | 25.3 | ECE | E11-106R-002968 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 32 | 35 | 38 | 41 | 44 | 46 | 49 | 52 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5070 | 6010 | 6480 | 6940 | 7410 | 7880 | 8360 | 8820 | - | - |
| 25 | 5070 | 6010 | 6480 | 6940 | 7410 | 7880 | 8360 | 8820 | - | - |
| 20 | 5470 | 6460 | 6960 | 7450 | 7950 | 8440 | 8940 | 9440 | - | - |
| 15 | 5670 | 6700 | 7210 | 7730 | 8240 | 8750 | 9270 | 9790 | - | - |
| 5 CYC. | 6260 | 7650 | 8360 | 9050 | 9740 | 10440 | 11130 | 11840 | 12530 | 13230 |
| STATIC | 9610 | 11750 | 12810 | 13880 | 14950 | 16020 | 17080 | 18140 | 19210 | 20280 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.