

# MP 567

<b>TIRE SIZE</b>	<b>12.0/75 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	IMPLEMENT MACHINERY / TELEHANDLER / IMPLEMENTS / TELEHANDLER / UNIVERSAL VEHICLE
<b>VERSION</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	126 A8
<b>LI/SS FREE ROLLING</b>	139 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94067541	<b>RC (IN)</b>	107.2
<b>SW (IN)</b>	11.7	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	36.0	<b>RIM ALT</b>	9; 11
<b>SLR (IN)</b>	16.8	<b>ECE</b>	E11-106R-006701

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>58</b>
<b>25 FR</b>	5360
<b>25 DW</b>	3740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.